

PRODUCT LIST

1 PERFORMANCE CHEMICALS FOR SYNTHETIC RESIN & RUBBER INDUSTRIES AND PAINT, INK & PIGMENT INDUSTRIES

1. Curing Agents for Epoxy Resins and Epoxy Resin Enamels
2. Pigment Dispersants (Oligomer Type)
3. Emulsifiers for Emulsion Polymerization
4. Stabilizer for Emulsions and Latexes
5. Resin Modifiers
6. Internal Antistatic Agents
7. Mold Releasing Agents
8. Printing Ink Binders
9. Compounding Ingredients for Paints and Printing Inks
10. Polyurethane Coating Materials
11. Pigment Dispersants (Surfactant Type)
12. Defoaming Agents
13. Plasticizer for Polyurethane-Based Sealant

2 PERFORMANCE CHEMICALS FOR COSMETICS, PHARMACEUTICALS, DETERGENTS AND AGRICHEMICALS

Performance Chemicals for Cosmetics

1. Base Materials for Shampoos (Anionic Type)
2. Base Materials for Shampoos (Amphoteric Type)
3. Foam Stabilizers and Thickeners for Shampoos
4. Base Materials for Body Washes
5. Base Materials for Hair Conditioners
6. Compounding Ingredients for Cosmetics
7. Emulsifiers for Cosmetics

Performance Chemicals for Pharmaceuticals

1. Tablet Binders
2. Base Materials for Ointments
3. Coating Agents for Tablets
4. Germicides (Pharmaceutical Use)
5. Other Products for Pharmaceuticals

Performance Chemicals for Detergents

1. Base Materials for Detergents
2. Germicides (Industrial Use)
3. Additives for Detergents
4. Base Materials for Household Softeners
5. Industrial Defoaming Agents

Performance Chemicals for Agrichemicals

1. Emulsifiers for Emulsifiable Concentrates
2. Dispersants for Granule Preparations

3 PERFORMANCE CHEMICALS FOR POLYURETHANE AND POLYURETHANE-RELATED INDUSTRIES

1. Polyether Polyols for Flexible Slabstock Polyurethane Foams
2. Polyether Polyols for Automobile Hot Molded Seat Cushions
3. Polyether Polyols for Automobile High-Resilient Molded Seat Cushions
4. Polyether Polyols for Crushpad Foams
5. Polyether Polyols for Rigid Polyurethane Foams
6. Polyfunctional Polyols
7. Example of Polyurethane Foam System
8. Polyether Polyols for CASE
9. Prepolymers and Raw Materials for Polyurethane Elastomers
10. Base Materials for Synthetic Leathers
11. Water-Borne Polyurethanes for Textile Processing
12. Polyurethane Emulsions for Adhesives
13. Polyurethane Emulsions for Coatings

4 PERFORMANCE CHEMICALS FOR LUBRICANT INDUSTRIES AND MACHINERY & METAL PROCESSING INDUSTRIES

1. Lubricating Oil Additives
2. Base Materials for Polyalkylene Glycol-Type Lubricants
3. Base Materials for Water-Soluble Quenchants
4. Base Materials for Hydraulic Fluids
5. Materials for Brake Fluids
6. Rust Inhibitors
7. Water-Soluble Cutting Fluids
8. Emulsifiers for Metal Working Oils
9. Base Materials for Metal Cleaners

5 PERFORMANCE CHEMICALS FOR RESOURCE EXTRACTION AND MINING INDUSTRIES

1. Polymer Flocculants
2. Dewatering Accelerator
3. Cold Flow Improvers
4. Lubricity Improver
5. Dewaxing Aids

6 PERFORMANCE CHEMICALS FOR WASTEWATER TREATMENT

1. Polymer Flocculants
2. Aminoalkyl Methacrylate Monomers

8 PERFORMANCE CHEMICALS FOR CONSTRUCTION AND PUBLIC WORKS

1. Flooring Materials
2. Polyurethane for Architectural Paints
3. Water Sealants
4. Waterproofing Agents
5. Concrete Admixtures
6. Dispersant for Manufacturing Cement Boards by Extrusion Molding
7. Frothing Agent for Bubble Mortar
8. Mud Dispersants for Drilling
9. Waste Mud Solidification
10. Polymer Flocculants for Gravel Washing Wastewater Treatment
11. Binder for Ceramics

9 ADHESIVES AND ADHESIVE-RELATED PRODUCTS

1. Pressure-Sensitive Adhesives (Cohesive Agents)
2. Potting Resins for Artificial Kidneys (Hollow-Fiber Type)
3. Resins for Anti-Corrosion Paints for Automobiles (for Improving Adhesion of Paints to Electrodeposition Steel)
4. Binders for Fiber-Finishing Agents
5. Polyurethane Emulsion for Bonding Plastics, Cloth and Wood
6. Binders for Fiberglass
7. Curing Agents for Epoxy Resins

9

ADHESIVES AND ADHESIVE-RELATED PRODUCTS

1. Pressure-Sensitive Adhesives (Cohesive Agents)
2. Potting Resins for Artificial Kidneys (Hollow-Fiber Type)
3. Resins for Anti-Corrosion Paints for Automobiles (for Improving Adhesion of Paints to Electrodeposition Steel)
4. Binders for Fiber-Finishing Agents
5. Polyurethane Emulsion for Bonding Plastics, Cloth and Wood
6. Binders for Fiberglass
7. Curing Agents for Epoxy Resins

IMPORTANT :

Before handling these products, refer to the current Material Safety Data Sheet for recommended protective equipment, and detailed precautionary and hazards information.

A portion of the printing costs for this printing paper is donated to the Japan Committee "Vaccines for the World's Children".

Printed in Japan on March 18, 2011 C871107 KURO, TAI (1000)

For detailed information, please contact Tokyo Area Sales & Marketing Office of Sanyo Chemical Industries, Ltd.

E-mail: sanyoproduct@sanyo-chemical.com

Fax: +81 - 3 - 3245 - 1697

URL: <http://www.sanyo-chemical.co.jp/>

Tel: +81 - 3 - 5200 - 3400

Address: No.10 Chuo Bldg., 5 - 6, Honcho 1 - chome, Nihonbashi, Chuo - ku, Tokyo 103 - 0023, Japan

1. Pressure-Sensitive Adhesives (Cohesive Agents)

Product	Principal Component (Product form)	Uses and Features
POLYTHICK 310-S	Polyacrylate solution of two-component type (Liquid)	POLYTHICK 310-S has good creep resistance. It is suitable for acetate substrates, because it contains no ester-type solvent.
POLYTHICK 410-SA	Polyacrylate solution of two-component type (Liquid)	POLYTHICK 410-SA has good adhesion at low temperatures and to wet surfaces. It is suitable for paper and synthetic film labels.
POLYTHICK 430-SA	Polyacrylate solution of two-component type (Liquid)	POLYTHICK 430-SA is a higher concentration type of POLYTHICK 410-SA.
POLYTHICK 470-S	Polyacrylate solution of one-component type (Liquid)	POLYTHICK 470-S has good adhesion at low temperatures and to wet surfaces. It is easy to handle because it is a one-component adhesive. It is suitable for adhesive sheets for automobile interior finish.
POLYTHICK 610-SA	Polyacrylate solution of two-component type (Liquid)	POLYTHICK 610-SA follows the curved surfaces of wires and coils well. It is suitable for polyester electric insulating tapes.
POLYTHICK 5423A	Polyacrylate solution of one-component type (Liquid)	POLYTHICK 5423A strongly adheres to non-polar substrates. It is easy to handle because it is a one-component adhesive. It is suitable for polypropylene bags and envelope-sealing tapes.
POLYTHICK 1001-S	Polyacrylate solution of one-component type (Liquid)	POLYTHICK 1001-S has good removability. It is easy to handle because it is a one-component adhesive. It is suitable for surface-protection sheets for steel and plastic plates.

Polyisocyanate-type and melamine-type curing agents can be used for two-component pressure-sensitive adhesives listed above.

2. Potting Resins for Artificial Kidneys (Hollow-Fiber Type)

	Principal Component (Product form)	Uses and Features
POLYMEDICA Products	Polyurethane of two-component type (Liquid)	These products are used for potting a hollow-fiber type artificial kidney (attaching hollow fibers to the housing apparatus), used for artificial dialysis. They are also used as a potting resin for home and industrial water purifiers.

3. Resins for Anti-Corrosion Paints for Automobiles (for Improving Adhesion of Paints to Electrodeposition Steel)

Product	Principal Component (Product form)	Uses and Features
CHEMIOX KA-098 (main component) CHEMIOX KC-810 (curing agent)	Blocked polyurethane solution of two-component type (Liquid)	These products are easy to handle because there is no restriction of pot life. They cure by heating from 120 to 140 °C for about 30 minutes. CHEMIOX KA-098 / CHEMIOX KC-810 : They are used as resins for anti-corrosion (chipping) paints for automobiles.
CHEMIOX KA-112 (main component) CHEMIOX KC-505 (curing agent)		CHEMIOX KA-112 / CHEMIOX KC-505 : They are best suited for improving adhesion between a steel plate, such as a cationic electrodeposited one, and PVC resin. (CHEMIOX products are mixed with PVC sol, and the resulting mixture is coated to a steel plate and then baked.) These products are also applicable to pre-coat metals (PCMs) for electrical home appliances. Mixing ratios and curing temperatures are as follows : CHEMIOX KA-098 / CHEMIOX KC-810 = 100 / 17, 140 °C CHEMIOX KA-112 / CHEMIOX KC-505 = 100 / 30, 140 °C

4. Binders for Fiber-Finishing Agents

Product	Principal Component (Product form)	Uses and Features
PERMARIN UA-150	Polyether-type polyurethane emulsion (anionic) (Liquid)	PERMARIN UA-150 forms a strong and elastic film, imparting high resiliency to cloth. It is mainly used for improving the tactile property.
PERMARIN UA-300	Polycarbonate-type polyurethane emulsion (anionic) (Liquid)	PERMARIN UA-300 is suitable as a binder for various fibers including synthetics. It forms a strong and elastic film, imparting high resiliency to cloth. It provides processed cloth with excellent washing resistance, dry cleaning resistance, and color fastness to rubbing. It is used for binders of printing paste and various finishing agents.
PERMARIN UA-310	Polycarbonate-type polyurethane emulsion (anionic) (Liquid)	PERMARIN UA-310 is suitable as a binder for various fibers including synthetics. It forms a strong and elastic film, imparting high resiliency to cloth. It provides processed cloth with excellent washing resistance, and dry cleaning resistance. It is used for binders of various finishing agents.

5. Polyurethane Emulsion for Bonding Plastics, Cloth and Wood

Product	Principal Component (Product form)	Uses and Features
UPRENE UXA-307	Polyester-type polyurethane emulsion (anionic) (Liquid)	UPRENE UXA-307 is best suited for bonding plastic sheets, plywood, and cloth. It is stable at pH 3 or higher. It can also be used as an adhesion improving additive for other emulsion-type adhesives. It particularly has high creep resistance.

6. Binders for Fiberglass

Product	Principal Component (Product form)	Uses and Features
MELPOL F-220	Modified polyether (Pellet)	MELPOL F-220 is used as a sizing agent for warp when weaving fiberglass. It can produce less fluffy glass cloth because it forms a flexible, spreadable film. It pyrolyzes at comparatively low temperatures (pyrolysis starts at approx. 250 °C), and leaves almost no residue after burning.
ACROBINDER BG-7	Copolymer of butadiene and maleic acid (Liquid)	ACROBINDER BG-7 is used for fiberglass reinforced thermoplastic resins.
CHEMITYLENE PEB-13ST	Bisphenol-type unsaturated polyester (Powder)	CHEMITYLENE PEB-13ST is used as a binder for glass chopped strand mats. It can produce flexible, high tenacity fiberglass mats due to its high affinity to fiberglass. It allows glass chopped strand mats to be easily permeated with unsaturated polyester resins because it has a structure similar to that of unsaturated polyester resins. It provides cured products with high transparency and heat resistance.

7. Curing Agents for Epoxy Resins

Product	Principal Component (Product form)	Uses and Features
POLYIMIDE L Products	Polyamideamine (Liquid)	These products are a variety of liquid polyamideamine-type curing agents for epoxy resins, and are assorted and divided into many grades with different amine values and viscosities. The resins cured with these products are durable and flexible, and show a marked adhesion to plastics and metals. These products are also suited as curing agents for adhesives and sealants used for civil engineering and construction work. See the table on page 4.
REACT CA-101	Modified polyamine (Liquid)	REACT CA-101 is liquid modified aliphatic polyamine-type curing agent for epoxy resins. It cures epoxy resins even at low temperatures. The curing reaction is influenced by carbon dioxide and moisture in air to a lesser degree. The resins cured with this product have excellent water resistance and chemical resistance. See the table on page 4.
DSA PDSA-DA	Alkenyl succinic anhydride (Liquid)	These products are succinic anhydride with a long alkenyl group. The resins cured with these products have excellent electrical properties and flexibility. See the table on page 4.

Appendix

1. Typical Properties of POLYIMIDE L Products

Product	Appearance	Color (Gardner)	Viscosity mPa · s	Amine Value
POLYIMIDE L-25-3	Brown liquid	6	3,800 (40°C)	285
POLYIMIDE L-45-3	Brown liquid	7	4,800 (40°C)	320
POLYIMIDE L-55-3	Straw-colored liquid	5	1,750 (20°C)	380
POLYIMIDE L-504	Brown liquid	6	2,000 (25°C)	300
POLYIMIDE L-2513	Brown liquid	6	2,250 (30°C)	290
POLYIMIDE L-4051	Straw-colored liquid	4	300 (20°C)	345

2. Typical Properties of REACT CA-101

Product	Appearance	Color (Gardner)	Viscosity mPa · s	Amine Value
REACT CA-101	Pale yellow liquid	3	4,000 (20°C)	430

3. Typical Properties of DSA and PDSA-DA

Product	Appearance	Color (Gardner)	Viscosity mPa · s	Acid Value
DSA	Yellow liquid	5	700 (20°C)	412
PDSA-DA	Straw-colored liquid	9	1,500 (20°C)	350

Alphabetical Index

ACROBINDER BG-7	3	POLYIMIDE L-45-3	4
CHEMIOX KA-098	2	POLYIMIDE L-55-3	4
CHEMIOX KA-112	2	POLYIMIDE L-504	4
CHEMIOX KC-505	2	POLYIMIDE L-2513	4
CHEMIOX KC-810	2	POLYIMIDE L-4051	4
CHEMITYLENE PEB-13ST	3	POLYTHICK 310-S	1
DSA	3, 4	POLYTHICK 410-SA	1
MELPOL F-220	3	POLYTHICK 430-SA	1
PDSA-DA	3, 4	POLYTHICK 470-S	1
PERMARIN UA-150	2	POLYTHICK 610-SA	1
PERMARIN UA-300	2	POLYTHICK 1001-S	1
PERMARIN UA-310	2	POLYTHICK 5423A	1
POLYMEDICA Products	1	REACT CA-101	3, 4
POLYIMIDE L Products	3	UPRENE UXA-307	2
POLYIMIDE L-25-3	4		